

General Specs

Sweep Path:

- Main broom only: 60"
- Main broom & one side broom: 90"
- Main broom and 2 side Brooms: 120"

Chassis Commercial Class 7

Wheel Base Chassis dependent

Warranty Sweeper, 1 year parts & labor

Engine (Freightliner M2)

Make M2 Cummins L9

Type 6 cylinder

Displacement 8.9 L

Horsepower 260 @ 2200 RPM

Torque 720 lb. ft. (976 Nm)

Aspiration Turbo charged

Main Broom

Type Prefab disposable

Polypropylene filled

Diameter 34" (864 mm)

Broom Material Polypropylene

Length 60" (1,524 mm)

Core Type Disposable steel tube

Speed Constant

Drive Hydraulic motor with direct drive

Digging Pressure & Wear Control

Closed loop hydraulic spring

Lift Control Hydraulic

Mounting Full-floating trailing arm

Down Pressure Indicator In cab dial

Side Broom

Type 5 or 6 segment plastic disposable

Diameter 46" (1188 mm)

Broom material 26" wire (660 mm)

Disc Construction Steel

Speed Adjustable on side of machine

Drive Full hydraulic

Digging Pressure & Wear Control

Pneumatic, from cab

Lift Control Pneumatic

Flexibility Free-floating and full sideways oscillation

Mounting Trailing Arm

Conveyor

Type Squeegee with replaceable rubber edging

Material (elevator bottom) Bolt-in multi section abrasion resistant steel plates

Speed Constant, forward and reverse

Flexibility Lift independent (for large object passage)

Drive (forward and reverse)

Hydraulic motor

Adjustment Hydraulic chain adjuster

Lift Control Hydraulic (independent of rear broom)

Ground Clearance Lifiable to 12" (305 mm) for bulk object passage

Cascade Washdown With fill diverter

Instrumentation/Controls

Warning Lamps & Buzzer

Low hydraulic oil

Conveyor stall

Warning Lamps

Hydraulic oil temperature

Hydraulic oil filter restriction

Low water spray

Broom position

Hopper position

Water tank level

Electrical System (Chassis)

Twelve Volt Negative Ground System

160 amp alternator

Battery 2- Group 31, 1850 CCA

Circuit Protection Activated by ignition switched constant duty solenoid (except lights)

Wiring Hot stamp identified with weatherproof connectors

Hydraulic System

Sweep System Pump

Variable displacement

Capacity 22 gpm

Fittings O-ring face seal

Reservoir Capacity 23 gal

Inlet Strainer 100 mesh

Return Filter 6 micron

Filter Restriction Indicator

Breather 10 micron

Cooler Externally mounted

Valves Electro-hydraulic

Hopper

Volumetric Capacity 4.5 yd³ (3.4 m³)

Material Volume 3.3 yd³ (2.5 m³)

Hopper Lift and Dump Controls

Electro/hydraulic in cab

Inspection Door

Offload

Right Side

Minimum dump height 38" (965 mm)

Maximum dump height 11' 2"

(3,404 mm)

Maximum hopper dump angle 50°

Design lift capacity 11,000 lb (4,990 kg)

Lifting mechanism Two stage scissors with hydraulic cylinders

Water Spray System

Tank Construction Polyethylene

Tank Capacity 360 gallons (1,362 L)

Fill Hose 15' 0" (4,572 mm) with 2.5" (64 mm) NST hydrant coupling

Pump Electric diaphragm

Spray nozzles 3 across main broom and over each gutter broom

Water Filter 80 mesh plastic housing

Controls In cab pump control and flow control valves at each side broom

Available Enhancements

- Outside cab, side broom down pressure control
- Outside cab, main broom down pressure control
- LED strobe
- Arrow stick
- Automatic lubrication system
- Fire extinguisher
- Broom Camera system (rear standard)
- Front spray bar
- Hydrant wrench
- Lighting bundles
- In cab side broom speed control

Paint

Body: High-gloss white powdercoat

Custom colors available

Undercarriage:

Grey powdercoat

Chassis

Freightliner M2, Autocar Xpert, or International 4400. Contact your Elgin Dealer for detailed chassis specifications.

Warranty

Sweeper

1 year parts and labor

Engine

Consult Factory

Your local Elgin Dealer is:



1300 W. Bartlett Road
Elgin, Illinois, U.S.A. 60120-7529
(847) 741-5370 Phone
(847) 741-3035 Fax
www.elginsweeper.com